

RosettaLigand Docking Tutorial


Rosetta Workshop – April 30, 2013

Darwin Fu (Darwinyfu@gmail.com)

Some quick and dirty terminology

- ❑ Ligand: small molecule binder (“drug-like”)
- ❑ Chain/jump: identifier for protein/ligand molecule
- ❑ Low-resolution/Coarse-grained: fast centroid or grid based sampling steps
- ❑ High-resolution/Atomistic: full-atom steps with complete Rosetta energy function
- ❑ Integer: 0,1,2,3,4...etc.
- ❑ Float: 1.2, 2.3, 0.78...etc.
- ❑ Boolean: True/False
- ❑ String: alpha/numeric/symbol combination


Ligand Docking and Rosetta



K. J. Gregory *et al.*, Probing the metabotropic glutamate receptor 5 (mGlu5) positive allosteric modulator (PAM) binding pocket: discovery of point mutations that engender a “molecular switch” in PAM pharmacology., *Molecular pharmacology* **83**, 991–1006 (2013).

A History of RosettaLigand

- Meiler and Baker 2006
 - ▣ Protein and ligand ensembles
 - ▣ Side chain flexibility
- Kaufmann et. al. 2008
 - ▣ Rotatable bond angle sampling
- Davis and Baker 2009
 - ▣ Backbone flexibility near binding site
- Lemmon and Meiler 2012
 - ▣ XML Scripts




HIV-1 PR homodimer (green/wheat) with acetylpepstatin (yellow) in binding site (red)

G. Lemmon et. al. *Chemical biology & drug design* (2012).

Now and Future

- Combs et. al. 2013
 - ▣ Docking into comparative models
- Allison et. al. 2013
 - ▣ Dock/design of interface
- Lemmon and Meiler 2013
 - ▣ Docking with interface waters
- Future Developments
 - ▣ High throughput screening
 - ▣ Membrane protein-ligand docking scoring
 - ▣ Docking congeneric ligands with structure-activity relationships



T4-Lysozyme Comparative Models

Combs et. al. (2013)

RosettaLigand Algorithm

**Low Resolution
Coarse Grained**

Initial Placement

Transform

**High Resolution
Atomistic**

Small ligand moves

Interface side-chain moves

Gradient based
minimization

Final minimization

Monte Carlo
accept/reject

“New is Always Better” —



Transform

Grid-Based Translation,
Rotation, and Conformer
sampling

Translate

Centroid-based Translation

Rotate

Grid-based Rotation

Slide Together

Translation to keep protein-
ligand contacts

Overview of XML Script

- SCOREFXNS
 - ▣ Soft-rep
 - ▣ Hard-rep
- SCORINGGRIDS
- LIGAND_AREAS
- INTERFACE_BUILDERS
 - ▣ Side-chain and backbone
- MOVEMAP_BUILDERS
 - ▣ Docking and Minimization
- MOVERS
 - ▣ StartFrom
 - ▣ Transform
 - ▣ HighResDocker
 - ▣ FinalMinimizer
 - ▣ InterfaceScoreCalculator

Low Resolution Steps High Resolution Steps Evaluation Steps

RosettaLigand Algorithm

Ensemble selection



Initial placement





Transform



Docking Cycles



High res refinement



RosettaLigand Algorithm

Ensemble selection



Initial placement




Transform



Docking Cycles



High res refinement



RosettaLigand Algorithm

Ensemble selection



Initial placement




Transform



Docking Cycles



High res refinement



StartFrom

<StartFrom name=(string) chain=(string)/>

<Coordinates x=(float) y=(float) z=(float)/>

<Coordinates x=(float) y=(float) z=(float)/>

</StartFrom>

Places the centroid of the ligand into the starting spot

- *Optional.* Provide a list of possible XYZ starting coordinates. One of these will be chosen at random for initial ligand placement.
- Can manually place ligand into using Pymol instead

RosettaLigand Algorithm

Ensemble selection



Initial placement



Transform




Docking Cycles




High res refinement



Grid based Monte-Carlo
Translation, Rotation, and
Conformation Sampling



Transform Algorithm




Simple Shape Complementarity



Red = Repulsion Teal = Attraction

Setting Up The Grid and Transform

Sampling Translation And Rotation (**STAR** protein)



Center: Initial center of ligand that acts as center of grids

Box size: The center of ligand cannot move outside this box

Grid Width: No ligand atoms are allowed outside this box

Translation: Random 3D translation between 0 and move distance (Gaussian distribution)

Rotation: Random 3D rotation between 0 and angle (Gaussian distribution)

Grid Manager

```
<SCORINGGRIDS ligand_chain=(string) width=(float)>  
  <classic grid_type="ClassicGrid" weight=(float)/>  
  <Another Grid>  
</SCORINGGRIDS>
```

Sets up scoring the grid(s) around the ligand

- Ligand_chain: Identifies the ligand to build around
- Width: Grid width to keep all atoms in
- GridType: Type of grid to use, classic grid is shape complementarity
- Weight: Scoring weight to use if we have multiple grids

Transform

```
<Transform name=(string) chain=(string) box_size=(float)  
  move_distance=(float) angle=(float) cycles=(int) repeats=(int)  
  temperature=(float)/>
```

Monte Carlo transformation of ligand in grid

- Chain: Ligand chain to move
- Box_size: Distance from starting position to restrain ligand center
- Move_distance: Max translational distance of a single move
- Angle: Max angular rotation of a single move
- Cycles: Number of Monte Carlo steps to perform
- Repeats: Number of times to perform cycles from starting position (EX: 3 repeats of 500 cycles means 1500 total steps)
- Temperature: Factor that controls determining how often an unfavorable move is accepted by Monte Carlo

RosettaLigand Algorithm

**Low Resolution
Coarse Grained**

Initial Placement

Transform

**High Resolution
Atomistic**

Small ligand moves


Interface side-chain moves

Gradient based
minimization

Final minimization

Monte Carlo
accept/reject

RosettaLigand Algorithm



HighResDocker

```
<HighResDocker name=(string) cycles=(int)  
  repack_every_Nth=(int) scorefxn=(string)  
  movemap_builder=(string) resfile=(string)/>
```

Atomistic Monte Carlo refinement of ligand and sidechain conformations

cycles: number of rotamer trials or repack steps (coupled w/small ligand movements).

repack_every_Nth: full repacks are interspersed with rotamer trials

scorefxn: Use a soft repulsive score here.

movemap_builder: movemap defined in the LIGAND AREA section

resfile: Specify what rotamer exchanges are possible (including design).

These are restricted to the defined interface region. Can be in options instead

RosettaLigand Algorithm

Ensemble selection



Initial placement



Transform



Docking Cycles



High res refinement

**Gradient Based
Minimization of side-
chain and backbone
torsion angles**

FinalMinimizer

```
<FinalMinimizer name=(string) scorefxn=(string)  
  movemap_builder=(string)>
```

Minimize the structure of the docked protein/ligand complex

scorefxn: Use a hard repulsive to remove clashes

movemap_builder: movemap defined in the LIGAND AREA
section

Move Maps, Interfaces, and Ligand Areas

<LIGAND_AREAS>

<inhibitor_dock_sc chain=X cutoff=6.0 add_nbr_radius=true all_atom_mode=false/>

<inhibitor_final_sc chain=X cutoff=6.0 add_nbr_radius=true all_atom_mode=false/>

<inhibitor_final_bb chain=X cutoff=7.0 add_nbr_radius=false all_atom_mode=true
Calpha_restraints=0.3/>

</LIGAND_AREAS>

<INTERFACE_BUILDERS>

<side_chain_for_docking ligand_areas=inhibitor_dock_sc/>

<side_chain_for_final ligand_areas=inhibitor_final_sc/>

<backbone ligand_areas=inhibitor_final_bb extension_window=3/>

</INTERFACE_BUILDERS>

<MOVEMAP_BUILDERS>


<docking sc_interface=side_chain_for_docking minimize_water=false/>

<final sc_interface=side_chain_for_final bb_interface=backbone minimize_water=false/>

</MOVEMAP_BUILDERS>


Move Maps, Interfaces, and Ligand Areas

Ligand area: identifies parameters for each ligand and identifies the atoms that are within a cutoff of the ligand




Move Maps, Interfaces, and Ligand Areas

Interface Builder: Extends those atoms to complete the residues



Move Maps, Interfaces, and Ligand Areas

Interface Builder: Extends to include surrounding residues for backbone flexibility



Move Maps, Interfaces, and Ligand Areas

Move map: identifies which residues are allowed to have backbone and side-chain movement. Typically, we have one for docking and one for minimization

Residue	Side-chain Movement	Backbone Movement
VAL 55	No	Yes
VAL 56	Yes	Yes
TYR 57	No	Yes
LEU 58	No	No

Move Maps, Interfaces, and Ligand Areas

□ LIGAND_AREAS

- cutoff: maximum distance between C-beta atom and ligand to still be part of interface
- add_nbr_radius: accounts for ligand atom size when computing cutoff distance
- all_atom_mode: uses all ligand atoms for identifying nearby residues


□ INTERFACE_BUILDERS

- extension_window: include “near-interface” residues for additional flexibility during backbone minimization

□ MOVEMAP_BUILDERS

- sc_interface: residues selected for repacking and rotamer trials
- bb_interface: residues selected for backbone ϕ/ψ adjustments

Scoring Compares Bound vs. Unbound



InterfaceScoreCalculator

InterfaceScoreCalculator

```
<InterfaceScoreCalculator name=(string)  
  chains=(comma separated chars) scorefxn=(string)  
  native=(string)/>
```

Calculates ligand-specific scores based on bound complex vs separated complex

chains: ligand chains to perform calculation for

scorefxn: Use a hard repulsive to identify clashes

native: native or “correct” structure for rms comparison if desired

The Params File

Residue Parameter Files define:

- Residue name and type
- Atom names, types, and charges
- Bonds, chi angles, and rotamers
- Internal coordinates
- Additional properties



Rosetta Database has existing parameter files for amino acids, but we need to generate custom ones for ligands

References

Methodology

- S. Combs *et al.*, Small-molecule ligand docking into comparative models with Rosetta, *Nature Protocols* **8**, 1277–1298 (2013).
- G. Lemmon, J. Meiler, R. Baron, Ed. RosettaLigand docking with flexible XML protocols, *Methods in Mol Biol* **819**, 143–155 (2012).
- I. W. Davis, D. Baker, RosettaLigand docking with full ligand and receptor flexibility., *Journal of molecular biology* **385**, 381–92 (2009).
- K.W. Kaufmann *et al.*, Small Molecule Rotamers Enable Simultaneous Optimization of Small Molecule and Protein Degrees of Freedom in ROSETTALIGAND Docking, German Conference on Bioinformatics, pp. 148–157 (2008)
- J. Meiler, D. Baker, ROSETTALIGAND : Protein – Small Molecule Docking with Full Side-Chain Flexibility, *Proteins* **548**, 538–548 (2006).

References

Applications

- K. J. Gregory *et al.*, Probing the metabotropic glutamate receptor 5 (mGlu5) positive allosteric modulator (PAM) binding pocket: discovery of point mutations that engender a “molecular switch” in PAM pharmacology., *Molecular pharmacology* **83**, 991–1006 (2013).
- B. Allison *et al.*, Computational design of protein-small molecule interfaces., *Journal of structural biology* (2013), doi:10.1016/j.jsb.2013.08.003.
- G. Lemmon, J. Meiler, Towards ligand docking including explicit interface water molecules., *PloS one* **8**, e67536 (2013).
- G. Lemmon, K. Kaufmann, J. Meiler, Prediction of HIV-1 protease/inhibitor affinity using RosettaLigand., *Chemical biology & drug design* **79**, 888–96 (2012).
- K. W. Kaufmann, J. Meiler, Using RosettaLigand for small molecule docking into comparative models., *PloS one* **7** (2012), doi:10.1371/journal.pone.0050769.
- K. W. Kaufmann *et al.*, Structural determinants of species-selective substrate recognition in human and *Drosophila* serotonin transporters revealed through computational docking studies., *Proteins* **74**, 630–42 (2009).

Today's Tutorial

□ Docking of eticlopride (antagonist) to Dopamine Receptor Subtype 3

Crystal Structure

Chien, E. Y. T. et al. Structure of the human dopamine D3 receptor in complex with a D2/D3 selective antagonist. Science 330, 1091–5 (2010)


Community Assessment

Kufareva, I. et al. Status of GPCR modeling and docking as reflected by community-wide GPCR Dock 2010 assessment. Structure 19, 1108–1126 (2011).

Rosetta Assessment

Nguyen, E. D. et al. Assessment and challenges of ligand docking into comparative models of g-protein coupled receptors. PLoS One 8, (2013)

Eticlopride, a D2/D3 selective antagonist in complex with D3 Receptor



Let's get started!

- ~/rosetta_workshop/ligand_docking
 - ▣ Prepare protein files in protein_prep
 - ▣ Prepare ligand files in ligand_prep
 - ▣ Perform docking in docking
 - ▣ All files in answer if you get stuck